

SEMI ELECTRIC STACKER

DYC

www.cnmhe.com

Make
Your Job
Easier



DYC

SEMI-ELECTRIC STACKER

MODEL			DYC10		DYC15		DYC20	
CHARACTERISTICS								
1.1	Capacity	Q	kg	1000	1500	2000		
1.2	Load center	C	mm	450	450	450		
1.3	Lifting height	H	mm	1600/2000/2500/3000/3500	1600/2000/2500/3000/3500	1600/2000/2500		
1.4	Lowered height of fork	H3	mm	85	85	85		
1.5	Fork length	L	mm	1000/1150	1000/1150	1000/1150		
1.6	Fork size		mm	54*160	54*160	54*160		
1.7	Fork width	E	mm	320~680	320~680	320~680		
1.8	Turing Radius	Wa	mm	1360	1360	1360		
1.9	Mast extend height	H2	mm	2065/2535/3035/3535/4035	2065/2535/3035/3535/4035	2065/2535/3035		
1.10	Mast lower height	H1	mm	2065/1580/1830/2080/2330	2065/1580/1830/2080/2330	2065/1580/1830		
1.11	Overall width	B	mm	790/900	790/900	790/900		
1.12	Overall length	A	mm	1690/1790	1690/1790	1690/1790		
1.13	Minimum ground clearance	H4	mm	30	30	30		
LIFTING SYSTEM								
2.1	Lifting speed(unladen/laden)		m/s	0.08~0.15	0.08~0.15	0.08~0.15		
2.2	Lowering speed(unladen/laden)		m/s	0.08~0.15	0.08~0.15	0.08~0.15		
2.3	Lifting motor		v/kw	12/1.5	12/1.5	12/1.5		
2.4	Battery capacity		v/ah	12/120	12/120	12/120		
2.5	Charger		v/a	12/15	12/15	12/15		
WEIGHT								
3.1	Weight		kg	380~460	380~480	380~480		

www.cnmhe.com

